

**Color Variants** 

BOP221102

Full glass door in Gaggenau Anthracite Width 60 cm

#### Included accessories

1 x enamel baking trav. suit. pyrolitic clean. 1 x glass pan. 1 x grill shelf.

BOP221102 Oven 200 series

Full glass door in Gaggenau Anthracite

Width 60 cm

Flush installation Pyrolytic system 9 heating methods, with baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 50 °C to 300 °C

# Net volume 76 litres Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

#### Handling

Rotary knob and TFT touch display operation. Information key with use indicators. Side-opening door opens up to 110° angle.

#### Features

Baking stone socket. Actual temperature display. Rapid heating. 60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe. Home network integration for digital services (Home Connect) either via cable connection LAN (recommended)

or wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: homeconnect.com.

# Safety

Thermally insulated door with quintuple glazing. Child lock Safety shut-off. Cooled housing with temperature protection.

# Cleaning

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

# Planning notes

Door hinge not reversible The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle. Min. 300mm distance to the adjacent wall is required.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

#### Characteristics

Color / Material Front

Anthracite

Built-in / Free-standing

Built-in Cleaning

Pyrolytic

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions (HxWxD)

595 x 590 x 547

Dimensions of the packed product (HxWxD)

770 x 710 x 660

Control Panel Material

**Door Material** 

Glass

Net weight 54.501

Usable volume of cavity

**Heating functions** 

Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot Air grilling, Top

First cavity material

Oven control

electronic

Number of interior lights

Approval certificates

CE, VDE

Length electrical supply cord

EAN code

4242006279899

Number of cavities (2010/30/EC)

**Energy efficiency rating** 

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC)

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

Connection Rating

3700

Fuse protection

Voltage

220-240

Frequency

fixed connection, no plug

# Consumption and connection features

2021-09-27

Page 1

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside the built-in niche.

The LAN port can be found at the back on the upper right side.

### Connection

Total connected load 3.7 KW. Plan a connection cable. Plan a LAN cable.



BOP221102 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm

2021-09-27 Page 2



